



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1071 OSCILLATING SPINDLE SANDER

Product Dimensions:

Weight.....	292 lbs.
Length/Width/Height.....	35-3/8 x 25-3/8 x 43 in.
Foot Print (Length/Width).....	16 x 16 in.

Shipping Dimensions:

Type.....	Cardboard
Content.....	Machine
Weight.....	296 lbs.
Length/Width/Height.....	29 x 26 x 37 in.

Electrical:

Switch.....	On/Off Paddle Switch with Safety Lock
Switch Voltage.....	110V
Cord Length.....	9 ft.
Cord Gauge.....	16 gauge
Minimum Circuit Size.....	15 amps at 110V, 10 amps at 220V
Plug Included.....	Yes

Motors:

Main

Type.....	TEFC Capacitor Start Induction
Horsepower.....	1 HP
Voltage.....	110/220V
Prewired.....	110V
Phase.....	Single
Amps.....	14/7A
Speed.....	1725 RPM
Cycle.....	60 Hz
Number Of Speeds.....	1
Power Transfer	Direct Drive
Bearings.....	Shielded and Permanently Lubricated

Main Specifications:

Table Info

Table Width.....	25 in.
Table Length.....	25 in.
Table Thickness.....	1-1/8 in.
Table Tilt.....	Left 45, Right 20 deg.
Table Opening.....	6-7/8 in.
Table Inserts.....	.2 in.
Floor To Table Height.....	35-1/2 in.

Spindle Info

Spindle Diameters.....	1/4, 3/8, 1/2, 5/8, 3/4, 1, 1-1/2, 2, 3, 4 in.
Spindle Lengths.....	5, 6, 9 in.
Spindle Speed.....	1725 RPM
Spindle Oscillations.....	72 SPM
Stroke Length.....	1-1/2 in.
Arbor Size.....	3/4 in.
Total Arbor Length.....	10-3/4 in.

Construction

Base Construction.....	Formed Steel
Stand Construction.....	Formed Steel
Table Construction.....	Ground Cast Iron
Frame Construction.....	Sheet Metal
Paint.....	Powder Coated

Other

No. Of Dust Ports.....	1
Dust Port Size.....	4 in.
Mobile Base.....	G8683

Other Specifications:

Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	ID Label on Center of Stand
Awards	Wood Magazine Top Value 1999
Assembly Time	45 minutes

Features:

- Features Ground Steel Table Inserts
- Includes Formed and Welded Steel Stand
- 100 Grit Sleeve Included for Each Spindle
- Cast Iron Table
- Table Tilts 45 deg.